



DRILL RODS

TECHNICAL SPECIFICATIONS

TYPE SIZE	ROD O.D. (mm)	ROD I.D. (mm)	COUPLING I.D. (mm)	THREADS PER INCH (T.P.I.)	THREAD CONNECTION**
METRIC					
50 MM	50.0	37.0	22.0	3	50 MM
42 MM	42.0	32.2	22.0	4	42 MM
33.5 MM	33.5	23.7	15.0	4	33.5 MM
DCDMA-BS ["W" series]					
HW	88.9	72.0	60.5	3	HW
NW	66.7	50.8	35.0	3	NW
BW	54.0	38.0	19.0	3	BW
AW	43.8	31.7	16.0	3	AW
EW	34.9	23.0	11.0	3	EW
WIRE LINE					
P-WL	114.3	103.4	-	3	P-WL
H-WL	88.9	77.8	-	3	H-WL
N-WL	69.9	60.3	-	3	N-WL
B-WL	55.6	46.0	-	3	B-WL
A-WL	44.5	34.9	-	4	A-WL
ALUMINIUM					
53 MM	53.3	37.0	22.0	3	50 MM
43 MM	43.2	31.0	22.0	4	42 MM
SE TYPE					
SE-50	50.5	41.7	22.0	3	SE-50
SE-43	43.0	34.6	19.0	4	SE-43
PERCUSSION-ROTARY					
K-140	140.0	125.0			3.1/2" API Reg
K-114	114.3	101.6			3.1/2" API Reg 2.7/8" API Reg
K-89 HD	89.0	76.4			2.3/8" API Reg 2.7/8" API Reg
K-76 HD	76.0	63.3			2.3/8" API Reg
K-76	76.4	67.0			2.3/8" API Reg
K-70	70.0	58.0			K-70
K-60	60.0	50.0			K-60

The standard effective lengths are 3.0 & 1.5 meters. Other lengths may be manufactured upon request.

All rods have right hand threads. Left hand threads can be manufactured if requested.

**Other thread connections may be manufactured -if dimensionally possible- upon request

ABBREVIATIONS

O.D.: Outer diameter, I.D.: Inner diameter, HD.: Heavy Duty

Technodrill constantly improves its products and therefore reserves the right to modify and change specifications without prior notice.